

**Description****COPPER-BASED GREASE**

To lubricate at high temperatures of over 1000°C. Excellent anti-grip, anti-corrosion and lubricant.

Details**Product specifications**

EFFECTIVE

HIGH TEMPERATURES

SAFE

INFO

Does not dry even in a saline environment

Over 1000°C

No contraindication

Physical-Chemical Properties

Colour and Appearance

Product

Coppery viscous liquid

Specific weight

0.64 kg/l

Fragrance

Characteristic

Recommended use

Very suitable for moulding plastic materials and for metal die casting. Ideal for preventing locking of engine head studs, for exhaust bends, for burner and/or boiler servo-mechanisms. Does not produce sludge or residues.

HOW TO USE

Shake the can for about one minute. When it is dispensed, the colour should be a good copper red to guarantee the micronised copper particles are mixed well. Always use the special spray nozzle to apply.

Packaging available

400ml Spray

The information in this technical sheet is based on the specifications and potential use known to us. However, this data does not imply any legal obligation or liability whatsoever.

REGISTERED OFFICE
Via Domenico Scarlatti, 26
20124 Milan



Commercial Offices and Plant
Corso Europa, 91 – 20020 Solaro (MI)
info@farmicol.com
Customer Service +39 02 84505409
www.faren.com